

Wall Plugin Power Supply SN1-24

Description

The power supply SN1-24 is designed to operate units requiring a 24V DC supply with 6W maximum power from the mains.

The SN1-24 is for indoor use only.

Mounting and Connecting

Note:

Ever disconnect the SN1-24 from the mains before you make changes on the 24V installation!

Connect the red cable to the terminal "+24V" (with KEM FA*, TCE* and KCE* terminal 50) and the white cable to terminal "-24V" or "24V GND" (with KEM FA*, TCE* and KCE* terminal 51). For the correct procedure refer to the unit's manual.

Put the SN1-24 into the wall socket.



Technical Data

Protection Class	II
Primary	
Supply voltage	100 – 240V AC $\pm 10\%$
Frequency	47 – 63 Hz
Connector	Euro Connector
Secondary	
Voltage	24V $\pm 3\%$
Current	250 mA max.
Power	6W max.
	short circuit proof

Ordering Information

IPS7-9 Steckernetzteil 24V / 6W

Contact

KEM Headquarter

Liebigstraße 5
85757 Karlsfeld
Germany

T. +49/8131/ 59 39 1-0
F. +49/8131/ 92 60 4

info@kem-kueppers.com

KEM Service & Repairs

Wetzeller Straße 22
93444 Bad Kötzing
Germany

T. +49/9941/ 94 23 0
F. +49/9941/ 94 23 23

info@kem-kueppers.com

*More distributors & partners can be found at:
www.kem-kueppers.com*

Your local partner:



www.kem-kueppers.com
info@kem-kueppers.com